



Tech Info Library

Applesoft: Internals--Error Processor Routines

Revised: 11/7/84
Security: Everyone

Applesoft: Internals--Error Processor Routines

=====
ERROR D412
Checks ERRFLG and jumps to HNDLERR if ONERR is active. Otherwise it prints
<cr> "?" <error message pointed to by X> "ERROR". If this is during program
execution then it also prints " IN " and the CURLIN.

HANDLERR F2E9
Saves CURLIN in ERRLIN, TXTPTR in ERRPOS, X in ERRNUM, and REMSTK in ERRSTK.
X contains the error code. See the Applesoft Reference Manual page 136 for
the value of X for a given error.

RESUME F317
Restores CURLIN from ERRLIN and TXTPTR from ERRPOS and transfers ERRSTK into
the 6502 stack pointer.

ISCNTC D858
Checks the Apple keyboard for a CTRL-C (\$83). Executes the BREAK routine
if there is a CTRL-C.

CHKNUM DD6A
Make sure FAC is numeric. See CHKVAL.

CHKSTR DD6C
Make sure FAC is a string. See CHKVAL.

CHKVAL DD6D
Takes the result of the most recent FAC operation and check this result for a
string or numeric variable. A TYPE MISMATCH ERROR results if FAC and C don't
agree.
On entry:
C set checks for strings
C clear checks for numerics.

ERRDIR E306
Causes ILLEGAL DIRECT ERROR if the program isn't running. X is modified.

ISLETC E07D

..TIL00082-Applesoft-Internals-Error_Processor_Routines.pdf

Checks A for an ASCII letter ("A" to "Z"). On exit C set if A is a letter.

PARCHK DEB2

Checks for "(", evaluates a formula, and checks for ")". Uses CHKOPN and FRMEVL then falls into CHKCLS.

CHKCLS DEB8

Checks at TXTPTR for ")". Uses SYNCHR.

CHKOPN DEBB

Checks at TXTPTR for "(".

CHKCOM DEBE

Checks at TXTPTR for ",".

SYNCHR DECO

Checks at TXTPTR for the character in A. TXTPTR is not modified. Normally exits through CHRGET. Exits with SYNTAX ERROR if they don't match.

Apple Tech Notes

Tech Info Library Article Number:82