

Tech Info Library

Pascal: Sending Output to the Printer

Revised: 10/8/84 Security: Everyone

Pascal: Sending Output to the Printer

Here is an example of printing to both screen and printer from a Pascal program. Without the delay procedure, everything would appear to happen at once, so we have it in the program only to improve the sense of sequence during execution.

```
program PRINT_OUTPUT;
  var OutFile: text;
  procedure DELAY;
    var Count: integer;
    begin
      for Count := 1 to 2000 do
    end; {Delay}
begin
  rewrite (OutFile, 'printer:'); {Declare the printer}
                                  {as a file.}
  writeln ('This is a test.'); {Output goes to the screen.}
  writeln (OutFile, 'This is a test.'); {Output goes to}
                                         {the printer.}
  DELAY;
  writeln ('This goes to the screen.');
  writeln (OutFile, 'This goes to the printer.');
  close (Outfile) {Close the file ".printer" and end.}
end. {Print_Output}
```

To change devices, simply change the "PRINTER:" in the REWRITE statement to the name of the output device. The program APPLE3:DISKIO is an example of writing to a disk file.

Apple Pascal can have as many as ten files open for input and output at one time; "OutFile" is only one. Additional files can be declared with additional REWRITE statements.

..TIL00123-Pascal-Sending_Output_to_the_Printer.pdf

Because Pascal treats output as a file, both of these examples work with Apple II and Apple III Pascal.

To transfer a text file to the printer, use the Filer "T" function. For example, to print the contents of GRAFDEMO.TEXT (found on APPLE3:), type "T", followed by "APPLE3:GRAFDEMO.TEXT, PRINTER:". (Don't include the quotation marks.) The directory of APPLE3: can be printed out by typing "E", followed by "APPLE3:, PRINTER:".

Apple Technical Communications

Tech Info Library Article Number:123