



Tech Info Library

Apple Scribe Printer: Configuration Table

Revised: 9/5/85
Security: Everyone

Apple Scribe Printer: Configuration Table

=====

System	SW-1 12345678	Cable Required
Apple III	11010000	A+B
Macintosh	11010000	C
Lisa	11010000	A+B
Apple IIc	11010000	E *
Super Serial	11010000	B
High Speed Serial	N/A	N/A

Key: 0 = off = open; 1 = on = closed
* - Using default port settings

Cables:	Letter	Part Number	Comments
	A	590-0029-00	Modem Eliminator
	B	590-0037-B	DB-25 to DB-25
	C	590-0169	DB-9 to DB 25
	E	590-0191-A	5-pin DIN to DB-25

Apple III Driver Configuration:

Driver	Data Configuration Block											
	0	1	2	3	4	5	6	7	8	9	A	B
RS-232	0E	00	10	10	10	00	13	11	DF	84	50	80
Printer	0E	00	10	10	10							

Super Serial Card Configuration:

	1	2	3	4	5	6	7
SW1	Off	Off	Off	On	Off	On	On
SW2	On	On	Off	Off	On	Off	Off

..TIL01058-Apple_Scribe_Printer-Configuration_Table.pdf

The jumper block should be pointing towards terminal.

The Apple Interface Manual, Apple Computer (UK) Ltd.

Tech Info Library Article Number:1058