

ProFile Hard Drive: Specifications (Discontinued)

	10/7/93			
Security:	Everyone			
ProFile Hard Drive: Specifications (Discontinued)				
This article last reviewed: 10 May 1985				
Model A9M0005 5 Megabyte (Discontinued) A9M0100 10 Megabyte (Discontinued)				
I. Technical Specifications				
1. Data Storage Characteristics:				
		A9M0100	A9M0005	
Data Capacity (formatted)				
	in megabytes:	10	5	
	Data Surfaces:	4	4	
	Heads per Surface:	1	1	
Track Spacing per inch:		345	254	
	Tracks per Surface:	306	152	
	Sectors per Track:	16	16	
S	Sectors per Surface:	4896	2432	
	Block Size			
	in bytes:	512	512	
5.25"	Floppy Equivalence:	70	35	
2. Drive Characteristics:				
	Average Seek Time			
	in milliseconds:	85	180	
Data Transfer Rate				
in megabits/sec:		5	5	
Rotational Start-up Time				
in seconds:		20	20	
Drive Ready to Operate				
in seconds:		120	60	
Rotational Speed				
	in RPMs +/- 1%:	3600	3600	

..TIL01128-ProFile_Hard_Drive-Specifications_Discontinued.pdf

```
Mean Time Between Failure:
                       in hours:
                                   10,000
                                             10,000
          --Winchester technology
    3. Interface:
         a. Type: 8-bit parallel
         b. Connector: DB-25
         c. Drives per Interface: 1
    4. Power Requirements:
         a. U.S.: 110 VAC, 35 Watts
         b. Europe: 230 VAC
         c. Drive power source internal to the ProFile.
    5. Environmental Requirements
         a. Temperature
              --Operating: 50 to 104 degrees F (10 to 40 degrees C)
              --Storage: -7.6 to 176 degrees F (-22 to 80 degrees C)
         b. Humidity
              --Operating: 20 to 80% noncondensing.
              --Storage: 1 to 95%
    6. Physical Characteristics
                  inches centimeters
         Height: 4.39 11.15
         Width: 17.28
                             43.89
         Depth:
                  8.81
                              22.38
                  pounds kilograms
         Weight: 11
                               5
II. Package
   With the 5 Megabyte or 10 Megabyte ProFile package:
      1. Apple ProFile hard-disk drive
      2. Apple ProFile Accessory Kit including:
           a. ProFile interface cable
           b. System-specific ProFile owner's manual
           c. Warranty and product registration
           d. User Input Report
      3. Included in the Apple II Accessory Kit:
           a. Catalyst II software
           b. Apple II SOS Driver and Utilities software
```

- c. Backup II software
- d. Apple II ProFile Interface Card
- 4. Included in the Apple III Accessory Kit:
 - a. Catalyst 2.0 software
 - b. Pascal ProFile Manager software

..TIL01128-ProFile_Hard_Drive-Specifications_Discontinued.pdf

- c. Backup III software
- d. Apple III ProFile Interface Card
- III. System Configuration

--Either ProFile may be used the following Apple personal computers:

- 1. IIe
 - a. RAM: Minimum of 64 kilobytes
 - b. Operating System: ProDOS Pascal 1.2
 - c. Interface Cards:
 - -- The difference bewteen the 5Mb and 10Mb ProFile Interface cards is the ROM at location C6. The ROM is 341-027 for the 5Mb Card and 341-0299-B for the 10 Mb.
- 2. Apple III
- 3. Macintosh XL

NOTE: The Macintosh XL containing a built-in 10-megabyte hard disk requires a Parallel Interface Card (Order A6BB101, obsolete).

Features

Controller automatically scans for error conditions, relocating marginal data blocks elsewhere on the hard disk, if necessary.

Copyright 1988 Apple Computer, Inc.

Tech Info Library Article Number:1128