



Tech Info Library

Apple ///: Color Video Port Pinouts (2/95)

Revised: 2/14/95
Security: Everyone

Apple ///: Color Video Port Pinouts (2/95)

=====

Article Created: 28 October 1985
Article Reviewed/Updated: 14 February 1995

TOPIC -----

This article provides a description of the Apple /// color video port.

DISCUSSION -----

DB-15 Connector Signal Description

- 1Shield Ground - Establishes electrical ground.
- 2 XRGB4 - One of 4 RGB outputs. Pins 2, 5, 9, & 10 are TTL outputs with instantaneous color information. A linear-weighted sum of these four signals will form a true 16 color RGB video signal.
- 3 SYNC - Composite negative synchronous signal.
- 4 PDI - Not used
- 5 XRGB1 - See pin 2 (one of 4 RGB outputs)
- 6 GND - Power & Signal Ground
- 7 -5V - Maximum load 200 mA
- 8 +12V - Maximum load 500 mA
- 9 XRGB2 - See pin 2 (one of 4 RGB outputs)
- 10XRGB8 - See pin 2 (one of 4 RGB outputs)
- 11BWVID - NTSC B&W Composite video with negative going sync, 1 volt peak to peak into a 75 ohm load.
- 12NTSC - NTSC Color video with negative going sync, 1 volt peak to peak into a 75 ohm load.
- 13GND - Power & Signal Ground
- 14-12V - Maximum load 200 mA
- 15+5V - Maximum load 1 Amp.

Article Change History:

14 Feb 1995 - Reviewed for technical accuracy, revised formatting.

Support Information Services

Copyright 1988-95, Apple Computer, Inc.

Tech Info Library Article Number:1423