



# Tech Info Library

## Apple IIGS: How To Print to Local & Network Printers

Revised: 8/20/89  
Security: Everyone

Apple IIGS: How To Print to Local & Network Printers

=====  
This article last reviewed: 8 August 1989

TOPIC -----

Is it possible to print to local printers from an Apple IIGS on an Apple II network?

The network in question has an Apple IIGS and an ImageWriter II in each work area. Each of these Apple IIGS systems is networked into a central office where they share a LaserWriter IINTX. Sometimes users need to print to the local printer, other times to the LaserWriter.

Can they do this while on the network without shutting down their machines and restarting with software locally? They are using network versions of AppleWorks with third party applications and E-mail.

DISCUSSION -----

Printing both locally and over the network depends on the application's method of selecting a slot for printing.

AppleWorks does provide a method for assigning a printing slot, allowing three printers to be defined in the Printer Information screen. To do this:

- 1) Set up the printer specifications for the local ImageWriter printer in slot #1.
- 2) Set up an ImageWriter printer for slot #7. (This is for the ImageWriter Emulator used in the LaserWriter.)
- 3) Choose the desired printer by going to the Main Menu/Other Activities/Printer Information screen and selecting a new Open-Apple-H printer.

If the third party programs allow a slot choice within the program, select slot #1 for the local printer and slot #7 for the network printer.

Prior to using a slot #7 printer (the network printer), use the Chooser application to select the appropriate network printer.

(NOTE: These descriptions assume the use of the printer port on the Apple IIGS.)

Copyright 1989 Apple Computer, Inc.

Tech Info Library Article Number:4047