



Tech Info Library

Access II: Use Version 1.2 With Apple IIGS

Revised: 10/4/89
Security: Everyone

Access II: Use Version 1.2 With Apple IIGS

=====
This article last reviewed: 13 September 1989

TOPIC -----

I use Apple IIe and Apple IIc systems to communicate with my server HP by typing:

```
in#2  
Control-A  
T
```

at the Applesoft BASIC prompt.

When I tried this on an Apple IIGS, it didn't work. I set all communication parameters from the Control Panel exactly the same as the hardware settings on the Super Serial Card.

I tried starting up from a System disk, running BASIC.SYSTEM, and typing the program:

```
10 PRINT CHR$(4),"in#2"
```

```
RUN
```

This doesn't seem like a good permanent solution. Apparently, my version of Access II doesn't work on the Apple IIGS. Should I look for other terminal emulation software?

DISCUSSION -----

There should be no problem with this procedure on an Apple IIGS. You are invoking the Terminal mode from the Super Serial Card firmware, which should work.

The firmware may not be in modem mode. If this is the case, the method should

be Control-I T instead of Control-A T. (Control-I T is the command for the Printer/Terminal mode of the firmware, Control-A T is for the Modem mode.)

Access II does work on the Apple IIGS if version 1.2 is used.

Another terminal package is "ASCII Express MouseTalk" from United Software Industries.

Shareware terminal packages are available from various bulletin boards, but without a terminal package, accessing a bulletin board would be difficult at best.

For more information, search under: "United Software"

Copyright 1989 Apple Computer, Inc.

Tech Info Library Article Number:4538