



Tech Info Library

Macintosh IIci Video: Supported Resolutions and Scan Rates

Revised: 7/9/92
Security: Everyone

Macintosh IIci Video: Supported Resolutions and Scan Rates

=====
Article Created: 12 March 1990
Article Last Reviewed: 8 July 1992
Article Last Updated:

TOPIC -----

I want to use a Zenith VGA monitor with the Macintosh IIci. The horizontal scan rate for the monitor is 31.49, and the hertz rate is 60-70. Can I adjust the scan rate on the Macintosh IIci, so that it will work with this monitor?

DISCUSSION -----

The Macintosh IIci RBV (RAM-Based Video) supports the following resolutions and scan rates:

ID1	ID2	ID3	Monitor type	Format	Vert.	Horiz.
0	0	0	Unsupported monitor (video halted)			
0	0	1	Unsupported monitor (video halted)			
0	1	0	Reserved for future use			
0	1	1	Apple High-Resolution Monochrome	640x480	66.7Hz	35KHz
0	1	1	AppleColor High-Resolution RGB	640x480	66.7Hz	35KHz
1	0	0	15-Inch Portrait Display	640x870	75Hz	68.86KHz
1	0	1	Reserved for future use			
1	1	0	Unsupported monitor (video halted)			
1	1	1	No external monitor (video halted)			

1=no connection; 0=grounded

For an analog RGB monitor to work on the Macintosh IIci, it needs to meet one of the above specifications.

Here are the pinouts for the Macintosh IIci RBV connector:

01	RED.GND	Red Video Ground
02	RED.VID	Red Video
03	CSYNC	Composite Sync.
04	MON.ID1	Monitor ID, Bit 1
05	GRN.VID	Green Video
06	GRN.GND	Green Video Ground
07	MON.ID2	Monitor ID, Bit 2
08	nc	(No Connection)
09	BLU.VID	Blue Video
10	MON.ID3	Monitor ID, Bit 3
11	C&VSYNC.GND	CSYNC & VSYNC Ground
12	VSYNC	Vertical Sync.
13	BLU.GND	Blue Ground
14	HSYNC.GND	HSYNC Ground
15	HSYNC	Horizontal Sync.
Shell	CHASSIS.GND	Chassis Ground

Copyright 1990 Apple Computer, Inc.

Tech Info Library Article Number:5336