



# Tech Info Library

## A/UX: MacX and Native X Performance (9/94)

Revised: 9/20/94  
Security: Everyone

A/UX: MacX and Native X Performance (9/94)

=====  
Article Created: 25 January 1991  
Article Reviewed/Updated: 19 September 1994

TOPIC -----

I need to optimize an A/UX system for running X Window System applications in the following environments:

- 1) Running Native X Window System under A/UX on a Macintosh IIcx, running with 16MB or 32MB of physical RAM.
- 2) Running MacX in the Finder under A/UX on Macintosh IIcx, running with 16MB or 32MB of physical RAM.

The applications are X based, using pull-down menus extensively. Of the two, running under MacX is going to be weighed most heavily. I will be using the MacX 1.2 that comes with A/UX.

Does running the same application in a rooted color window versus rootless color window affect performance one way or the other?

I've used the following method to optimize A/UX for Native X Window System under 8MB of memory:

For systems with 8MB, bring A/UX up as single-user, then run these commands:

```
# kconfig -n /unix
NBUF=2500
NINODE=600
NFILE=400
<Control-D>
# sync
# sync
# sync
```

# reboot

When doing this though, MacX performance under A/UX on the same machine crawls slower than before.

DISCUSSION -----

Performance should not be affected when selecting a rootless color window or a rooted color window when running the same X client application.

The above kernel parameters, especially NBUF=2500, seems to be too high for an A/UX 8MB system. The "NBUF=2500" itself takes up 5MB (2500 x 2K) of existing memory. When you add the other kernel parameters, there is not much available physical memory left for applications. This will cause more paging activity and, in turn, degrade the performance.

If you have 16MB or 32MB of physical memory on a Macintosh IIfx running A/UX 3.0, the same kernel parameters configuration should be feasible to run either X11 Window System or MacX under A/UX.

The system performance will really depend on how many X client applications and other applications, including Macintosh applications and UNIX processes, are running at the same time in A/UX and the underlying network environment in which A/UX resides. The following kernel parameters should be adjusted accordingly to fit your running environment:

NBUF If NBUF=0, it allocates about 10% of free memory for disk block I/O buffers.

NFILE is the size for system file-table pool (600 seems fair enough).

NINODE is the size for system inode-table pool (400 seems fair enough).

NPROC is the maximum number of processes allowed in the system.

MAXUP is the maximum number of processes per user allowed in the system.

NMIBUFS is the maximum number of buffers allocated for networking.

Each NMIBUFS buffer requires 256 bytes. The more network daemons running, the more mibufs are needed for memory allocation.

Since both MacX and X11 must be run at least in an A/UX B-Net kernel, the NMIBUFS must be set fair enough for the network buffering. By default, 500 mibufs are allocated. For an A/UX with NFS and/or YP A/UX kernel, the NMIBUFS needs to be increased significantly, say 1000 or 1500.

The "netstat -m" can be used to display the number of mibufs currently in use.

Also, the "pstat -m" command can be used to display information about the current memory allocations, which include the number of I/O buffers (NBUF) allocated, the number of inodes (NINDOE), and the file (NFILE) currently active.

Article Change History:

19 Sep 1994 - Reviewed for technical accuracy.

31 Aug 1992 - Reviewed for technical accuracy.

Support Information Services

Copyright 1991-94 Apple Computer, Inc.

Tech Info Library Article Number:6706