

AppleCD SC Plus: Specifications (Discontinued)

Revised: 10/7/93 Security: Everyone

AppleCD SC Plus: Specifications (Discontinued)

Article Created: 21 June 1991

TOPIC -----

This article gives the technical specifications for the AppleCD SC $\$ Plus CD-ROM drive.

DISCUSSION -----

The playback medium for the AppleCD SC Plus is a 12-centimeter optical disc installed in a CD caddy. Any CD-ROM or audio compact disc is compatible.

The data capacity in mode #1 is 656MB, 748MB in mode #2. The unit access is from 1 recording surface. The unit has a capacity of more than 270,000 blocks per disc. Data per block is 2,048 bytes in mode #1, 2,336 bytes in mode #2.

Audio playback time is more than 1 hour with a frequency response of 20 to 20,000 hertz.

Characteristics include

• Typical access time is 380ms (including latency).

The maximum first to last block access time is typically 650ms.

- The data streaming rate is 150K/second in mode #1, 171K/second in mode #2.
- The block rate is 75 blocks/second.
- SCSI bus transfer burst rate is 1.5MB/second.
- Rotational speed is approximately 230 to 530 rpm (variable).
- Startup time is typically 5 seconds, but media-dependent.
- Spin-down time is typically 2 seconds.

Electrical requirements

- 100 to 240 volts AC for line voltage
- Frequency is 50 to 60 hertz with maximum power of 40 watts.

..TIL07406-AppleCD_SC_Plus-Specifications_Discontinued.pdf

Environmental requirements

- Operating temperature: 50 to 104 degrees Fahrenheit (10 to 40 degrees Centigrade)
- Storage temperature: -22 to 122 degrees Fahrenheit (-30 to 50 degrees Centigrade)

Depth: 10.47 in. (26.6 cm) Weight: 8.8 lb (8 kg)

Copyright 1991 Apple Computer, Inc.

Tech Info Library Article Number:7406