



# Tech Info Library

## Apple II 3.5 Disk Controller Card: Specifications (2/97)

Revised: 2/12/97  
Security: Everyone

Apple II 3.5 Disk Controller Card: Specifications (2/97)

=====

Apple II 3.5 Disk Controller Card: Specifications (2/97)

Article Created: 11 December 1991  
Article Reviewed/Updated: 12 February 1997

### TOPIC -----

This article gives technical specifications for the Apple II 3.5 Disk Controller Card. This card has been discontinued by Apple.

### DISCUSSION -----

#### Overview

-----

The Apple II 3.5 Disk Controller Card allows you to use the 3.5-inch floppy disk drives, including the Apple SuperDrive and Apple 3.5 Drive, with an Apple IIGS or Apple IIe computer. The card also supports the operation of older model Apple II UniDisk 3.5 drives with the Apple IIe computer. This card replaces the UniDisk 3.5-inch Controller Card.

#### Drives Supported

-----

Apple SuperDrive

Apple 3.5 Drive

Apple UniDisk 3.5 Drive (Apple IIe only)

#### Specifications

-----

Microprocessor: 65C02

Disk controller: SWIM

Memory: 32K SRAM 32K ROM

Connector: DB-19

Power: Less than 4 watts

Environmental Requirements

-----  
Operating temperature: 50 to 104 degrees F (10 to 40 degrees C)

Storage temperature: 50 to 140 degrees F (10 to 60 degrees C)

Relative humidity: 20% to 80% noncondensing

Article Change History:

12 Feb 1997 - Reviewed for technical accuracy, revised formatting.

Copyright 1991-97, Apple Computer, Inc.

Tech Info Library Article Number:9292