Tech Info Library

Macintosh IIvx Compared to Other Apple Products

Revised: 10/15/92
Security: Everyone

Macintosh IIvx Compared to Other Apple Products

==========

Article Created: October 19, 1992

TOPIC ----------

The following table compares the Macintosh IIvx with other Apple products.

	IIsi	IIvi	Performa 600	IIci	IIvx
Processor	68030	68030	68030	68030	68030
Clock	20 MHz	16 MHz	32 MHz	25 MHz	32 MHz
Motherboard Clk	20 MHz	16 MHz	16 MHz	25 MHz	16 MHz
Cache	-	-	-	32K *	32K
FPU	Optional	Optional	Optional	Included	Included
Max DRAM	17MB	68MB	68MB	128MB	68MB
NuBus	see "Other slots"	3	3	3	3
Power Supply	65 Watts	112 Watts	112 Watts	90 Watts	112 Watts
Other slots	PDS/NuBus adapter	Accelerator	Accelerator	Cache*	Accelerator
Video	DRAM	512K VRAM	512K VRAM	DRAM	512K VRAM
Video Expansion	via NuBus or PDS	to 1MB	to 1MB	via NuBus	to 1MB

* 32KB cache occupies the "Cache" slot. Most Macintosh IIci systems

ship with cache.

	IIsi	IIvi	Performa 600	IIci	IIvx
12" Mono	256 gray	256 gray	256 gray	256 gray	256 gray
12" Color	256 color	256-32,000	256-32,000	256 color	256-32,000
13"/14" RGB	256 color	256-32,000	256-32,000	256 color	256-32,000
15" Portrait	16 gray	-	-	16 gray	-

	IIsi	IIvi	Performa 600	IIci	IIvx
Internal Storage	SuperDrive 3.5" x 1"	SuperDrive 3.5" x 1/2H 5.25" removable	SuperDrive 3.5" x 1/2H 5.25" removable	SuperDrive 3.5" x 1"	SuperDrive 3.5" x 1/2 5.25" removable
Mic Input	X	X	X	-	X
CD Audio In	-	X	X	-	X
External SuperDrive	X	-	-	X	-
ADB	1	2	2	2	2
Performance relative to a Classic (mono)	4.7	3.7	5.1	6.6	7.0
Relative to LC (8-bit color)	1.3	1.6	1.9	2.4	2.6

Copyright 1992, Apple Computer, Inc.

Tech Info Library Article Number:10782