



Tech Info Library

Centris 610: Specifications-Discontinued (8/94)

Revised: 8/31/94
Security: Everyone

Centris 610: Specifications-Discontinued (8/94)

=====
Article Created: 9 February 1993
Article Reviewed/Updated: 31 August 1994

TOPIC -----

This article provides technical specifications for the Macintosh Centris 610 computer.

DISCUSSION -----

Microprocessor

- MC68LC040, 20-MHz clock speed, main logic board clock 20 MHz; 32-bit data bus; no floating point unit (FPU)
- Integral Paged Memory Management Unit (PMMU) and 8K-cache architecture

Memory

- Comes with 4MB of RAM on the logic board
- Expandable to 68MB of RAM by adding Single Inline Memory Modules (SIMMs) to two 72-pin slots. (Doesn't support 1MB, 2MB, or 64MB 72-pin SIMMs.)
- Includes RAM disk software

ROM

- 1MB

Disk Drives

- One built-in Apple SuperDrive 1.4MB floppy disk drive
- One internal 80MB, 230MB, or 500MB hard disk (500MB configuration not available in the U.S.)
- Accommodates one 5.25-inch half-height device, such as the AppleCD 300i internal CD-ROM drive

Video Display

- Supports all Apple displays
- Works with a wide range of third-party displays, including some 19-in., VGA, SVGA, NTSC, and PAL monitors

Video RAM (VRAM)

512K Standard Supports:

- 32,768 colors on the Macintosh 12-inch RGB Display
- 256 colors on the AppleColor High-Resolution RGB Display (13"), Macintosh Color Display (14"), and Macintosh 16-inch Color Display
- 256 shades of gray on the Macintosh 12-inch Monochrome Display
- 16 shades of gray on the Macintosh Portrait Display (15")
- 16 colors on the Macintosh 21-inch Color Display

1,024K Option Supports:

- 32,768 colors on the Macintosh 12-inch RGB Display, AppleColor High-Resolution RGB Display (13"), Macintosh Color Display (14"), and Macintosh 16-inch Color Display
- 256 shades of gray on the Macintosh 12-inch Monochrome Display and Macintosh Portrait Display (15")
- 256 colors on the Macintosh 21-inch Color Display

Interfaces

- Internal expansion slot for one processor-direct or 7-inch NuBus expansion card (requires adaptor)
- SCSI interface for connecting up to six external peripheral devices
- AAUI-15 Ethernet connector (optional)
- Two serial (RS-232/RS-422) ports
- One video port for color and monochrome displays of various sizes and resolutions
- One sound-output port (stereo) for external amplifier or headphones, and CD playthrough
- One sound-input port for monaural sound input
- Two Apple Desktop Bus (ADB) ports for a keyboard, mouse, and other devices

Sound Generator

- Custom integrated circuit that drives a stereo miniature headphone jack (22 kHz sample rate)

Keyboard and Mouse

- Several ADB keyboards with numeric keypads available
- Apple Desktop Bus Mouse II

Clock/Calendar

- Custom integrated circuit with long-life lithium battery

Disability Access

CloseView, Easy Access, and visible-beep software are built in. These and third-party options provide alternative input and output devices

Power Requirements

-
- Line voltage: 100 to 240 V AC, RMS single phase, automatically configured
 - Frequency: 47 to 63 Hz
 - Power: 86 W maximum, not including display power

ADB power Requirements

-
- Maximum current draw for all ADB devices: 500 mA
(three ADB devices maximum recommended)
 - Mouse draws 10 mA
 - Keyboard draws 25 to 80 mA (depending on the model used)

Size and Weight

Main Unit:

-
- Height: 3.4 in. (8.5 cm)
 - Width: 16.3 in. (41.5 cm)
 - Depth: 15.6 in. (39.7 cm)
 - Weight: 14.0 lbs (6.4 kg) Weight varies depending internal devices installed.

Mouse:

- Height: 1.3 in. (3.3 cm)
- Width: 2.4 in. (6.2 cm)
- Depth: 4.2 in. (10.7 cm)
- Weight: 4.0 oz. (0.10 kg)

Operating Environment

-
- Operating temperature: 50 to 104° F (10 to 40° C)
 - Storage temperature: -40 to 116.6° F (-40 to 47 °C)
 - Relative humidity: 5% to 95% noncondensing
 - Maximum altitude: 10,000 ft. (3,048 m)

Article Change History:

- 31 Aug 1994 - Corrected processor to be 68LC040.
- 11 Aug 1993 - 500MB drive is not available in the U.S.

Copyright 1993-94, Apple Computer, Inc.

Tech Info Library Article Number:11376