

SNA•ps 3287 1.1.1 Release Notes (2/93)

Revised:	3/8/93
Security:	Everyone
SNA•ps 3287 1	.1.1 Release Notes (2/93)
Article Creat	ed: 19 February 1993
TOPIC	
This article	describes the release notes of SNA•ps 3287 1.1.1.
DISCUSSION	
	8 Release (v1.1.1)
• Text file o	output now properly converts unwanted control codes in the data o characters that are handled properly by text editors.
	andling end-of-bracket markers during output to text file was original symptom was a failure to append subsequent data to le.
	the OpenSession code that prevented use of translation tables US English was fixed.
look more l printed mod providing o Printing Ma print, and interval); machine exc current Las driver. The open the Pr	ace to the Macintosh Printing Manager was reworked to ike a "normal" Macintosh application: the entire print job is now Mally, with background printer spoolers such as PrintMonitor optimal response time. Previously, the connection to the mager was established as soon as the session had data to not closed until the print job timed out (a potentially long during this interval the user could muck around with the sept on direct-connect printers: mucking around is OK on the serWriter driver and is deadly on the current ImageWriter a change in 1.1.1 is to wait until the job times out, and then finting Manager connection, print the entire job, and close the This eliminates the ability to muck around (which may not be

safe on future or other network-connected printer drivers) and eliminates the long interval during which the Printing Manager connection was kept

..TIL11684-SNA-ps_3287_1-1-1_Release_Notes_2-93.pdf

open on direct-connect printers even if they supported print spooling.

• Because of the changed interface to the Printing Manager, the default timeout setting was changed to include a 200-page timeout limit. This is because at the default memory size of 512K, we can guarantee having enough memory to accumulate and then print 200 pages without running out of memory, and the changed Printing Manager interface means that we accumulate data until an entire job has arrived (as opposed to printing each page as it arrives). Otherwise, if print jobs arrive without the default timeout gap of 30 seconds, we would eventually run out of memory and stop receiving -- and thus never print the job until the user intervened and customized the timeout settings. The new default setting simply guarantees that SNA•ps 3287 can be installed and used without fine-tuning the timeout settings even if print jobs arrive continuously.

Known Problem Areas

• Printing on the LaserWriter driver with background printing turned off (and therefore under System 6.x with MultiFinder turned off) does not work.

Copyright 1993, Apple Computer, Inc.

Tech Info Library Article Number:11684