



Tech Info Library

HyperCard: getHandler Script (7/92)

Revised: 12/21/93
Security: Everyone

HyperCard: getHandler Script (7/92)

=====

Article Created: 11 January 1991
Article Reviewed/Updated: 23 July 1992

TOPIC -----

Given the name of a handler and a script, the following handler gets the text of the specified handler. Optionally, it will return starting and ending character expressions of the handler.

DISCUSSION -----

Script:

```
function getHandler handlerName,scriptText,returnOffsets
-- Extracts a handler from a script.
-- Given the name of a handler and a script, this handler gets
-- the text of the specified handler. Optionally, it will
-- return starting and ending character expressions of the handler.
-- check for function first because on is a substring of function

get offset("function " & handlerName,scriptText)
if it is zero then get offset("on " & handlerName,scriptText)
put it into startChar
put return & "end " & handlerName into footer
put offset(footer,scriptText) into endChar
if endChar is not zero then
  add length(footer) to endChar
  repeat until char endChar of scriptText is return ~
    or char endChar of scriptText is empty -- skip comment
    add 1 to endChar
  end repeat
  repeat while char endChar + 1 of scriptText is return
    add 1 to endChar -- take trailing returns
  end repeat
end if
if returnOffsets is true
```

```
    then return startChar & "," & endChar  
    else return char startChar to endChar of scriptText  
end getHandler
```

This article is adapted from the Claris Tech Info database.

Copyright 1993, Apple Computer, Inc.

Tech Info Library Article Number:14249