



Tech Info Library

Network Terminology and AppleTalk Limitations (5/94)

Revised: 5/25/94
Security: Everyone

Network Terminology and AppleTalk Limitations (5/94)

=====
Article Created: 25 May 1994

NETWORKING TERMINOLOGY

=====
Router: Connects 2 or more networks using the network layer.
Gateway: Manages communications between different protocol families.
Bridge: Connects 2 or more networks using the data link layer.
Hop: Used to describe a jump through a router to the next network.
AppleTalk: The network protocol for Apple Macintosh Systems.
LocalTalk: AppleTalk protocol on twisted pair cabling (ie, PhoneNet).
EtherTalk: AppleTalk protocol on EtherNet cable with interface card.
TokenTalk: AppleTalk protocol on TokenRing cabling with interface card.

AppleTalk Information:

-
- Phase I supports up to 254 nodes, by number.
 - Phase II supports (theoretically) 16 million nodes by range or number.
 - LocalTalk should only address up to 32 nodes.
 - LocalTalk Network is identified by a single network number.
 - Extended AppleTalk networks are identified by network range.
 - Extended AppleTalk networks support zone lists.

OSI Model (applies to TCP/IP and other networking protocols):

- Layer 7 - Application
- Layer 6 - Presentation
- Layer 5 - Session
- Layer 4 - Transport
- Layer 3 - Network
- Layer 2 - Data link
- Layer 1 - Physical

Topology:

- Bus: All nodes connected in one line (daisy chain).
- Star: All nodes connected to a central hub.

Ring: All nodes connected in a closed loop.

Support Information Services

Copyright 1994, Apple Computer, Inc

Tech Info Library Article Number:15464