



# Tech Info Library

## Power Macintosh 7200/75 & 7200/90: Specifications (9/96)

Revised: 9/23/96  
Security: Everyone

Power Macintosh 7200/75 & 7200/90: Specifications (9/96)

=====  
Article Created: 6 July 1995  
Article Reviewed/Updated: 10 September 1996

TOPIC -----

This article contains a list of technical specifications for the Power Macintosh 7200/75 and 7200/90.

DISCUSSION -----

### Microprocessor

- PowerPC 601 microprocessor running at 75 MHz (7200/75 model)
- PowerPC 601 microprocessor running at 90 MHz (7200/90 model)
- Integrated floating-point unit and 32K cache

### Memory

- 8 MB of RAM, expandable to 256 MB via 4 DIMM sockets  
(Note: There is no RAM soldered to the logic board. The DIMM sizes installed at the factory will vary according to availability; there will be either two 4 MB DIMMs or one 8 MB DIMM.)
- Level 2 (L2) Cache: L2 Cache Slot for Optional 256KL2 cache on a 160-pin DIMM. (These computers theoretically support 512K and 1 MB of L2 cache, but these configurations have not been tested and are not supported by Apple.)
- 4 MB of ROM
- 1 MB of Video RAM (VRAM) in both the Power Macintosh 7200/75 & 7200/90 models

### Disk Drives

- Internal 500 MB SCSI hard disk
- Internal Apple SuperDrive floppy disk drive
  - Accepts high-density 1.4 MB disks and 800K disks
  - Reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks

- Internal AppleCD 600i quadruple-speed CD-ROM drive
- Expansion bay for additional 3.5-inch hard disk

#### Interfaces

- 
- Three PCI expansion slots compatible with PCI 2.0-compliant cards  
(Note: These slots are not NuBus-compatible)
  - Two high-speed DMA serial (RS-232/RS-422) ports compatible with LocalTalk and GeoPort cables
  - 10Base-T and AAUI-15 Ethernet connectors
  - Internal and external SCSI bus (up to 5 MB/s)
  - Apple Desktop Bus (ADB) expansion port
  - Mini jacks for stereo audio input and output
    - 16-bit audio
    - Up to 44.1-kHz sampling rate
  - DB-15 connector for monitor

#### Audio System

- 
- Custom sound circuitry, including stereo generator (digital-to-analog converter, or DAC)—capable of driving stereo miniplug headphones or audio equipment—and stereo sampling hardware (analog-to-digital converter, or ADC) for recording stereo sound
  - 16-bit stereo input and output
  - Sample rates of 44.1 and 22.05 kilohertz (kHz)
  - Input line level: 2 volts peak-to-peak nominal, into 6.5-Kilohm (k ) impedance
  - Output line level: 2.2 volts peak-to-peak nominal, into 1 k impedance
  - Input through output SNR\*: >74 decibels (dB) typical
  - Bandwidth: 10 Hz-19 kHz (+/- 2 dB) at 44.100 kHz sample rate
  - THD+N\*: Less than 0.06%; measured 30 Hz-16 kHz with a 2-Vpp sine wave input
- \*SNR is signal-to-noise ratio; THD+N is total harmonic distortion plus noise.

#### Graphics Support

- 
- VRAM-based accelerated graphics
  - 1 MB of VRAM, expandable to 4 MB
  - 64-bit data path to VRAM (with 2 MB of VRAM)
  - Support for display resolutions of up to 1,280 by 1,024 pixels
  - 24-bit color of up to 1,024- by 768-pixel resolution
  - Refresh rate of up to 75 Hz

#### GeoPort Telephony\*

- 
- 14.4-Kbit/s modem support
  - V.17 fax support
  - GeoPort Fax and GeoPort Telephony software included
  - Speakerphone and answering-machine capability
- \* Requires GeoPort Telecom Adapter

#### Clock/Calendar

-----

- Custom integrated circuit with long-life battery

#### Keyboard And Mouse

-----

- Supports ADB keyboards with numeric keypads
- Comes with an ADB Mouse II

#### Electrical Requirements And Compliance

-----

- Line voltage: 100 to 240 V AC, RMS single phase
- Frequency: 50 to 60 Hz, single phase
- Power: 150 W maximum, not including display
- Energy Star compliant

#### ADB Power Requirements

-----

- Maximum current draw for all devices: 500 mA  
(a maximum of three ADB devices is recommended)
- Mouse draws 10 mA
- Keyboard draws 25 to 80 mA (varies with keyboard used)

#### Size And Weight

-----

- Height: 6.15 in. (15.6 cm)
- Width: 14.37 in. (36.5 cm)
- Depth: 16.93 in. (43.0 cm)
- Weight: 22 lb. (9.97 kg)

#### Operating Environment

-----

- Operating temperature: 50 degrees to 104 degrees F  
(10 degrees to 40 degrees C)
- Storage temperature: -40 degrees to 116 degrees F  
(-40 degrees to 47 degrees C)
- Relative humidity: 5% to 95% noncondensing
- Maximum altitude: 10,000 ft. (3,048 m)

#### Article Change History:

- 10 Sep 1996 - Clarified cache information.
- 12 Jul 1996 - Modified title.
- 08 Feb 1996 - Added VRAM info for 7200/90.

Copyright 1995-96, Apple Computer, Inc.

Tech Info Library Article Number:18083