



# Tech Info Library

## Power Macintosh 5260/120: Specifications (10/96)

Revised: 10/31/96  
Security: Everyone

Power Macintosh 5260/120: Specifications (10/96)

=====  
Article Created: 18 September 1996  
Article Reviewed/Updated: 31 October 1996

TOPIC -----

This article contains the technical specifications for the Power Macintosh 5260/120.

DISCUSSION -----

### Microprocessor

- =====  
\* PowerPC 603e processor running at 120 MHz  
\* 32K internal cache  
\* Integrated floating-point unit  
\* 40-MHz, 64-bit bus  
\* Optional 256K level 2 cache

### Memory

- =====  
\* Comes with 16 MB of RAM  
\* Can be expanded to 64 MB  
\* Uses 72-pin, noncomposite, 70-nanosecond or faster SIMMs

### Disk drives

- =====  
\* Internal 1.2GB IDE hard disk drive  
\* Internal Apple SuperDrive floppy disk drive  
- Uses high-density, 1.4MB floppy disks  
- Reads, writes, and formats Macintosh, Windows, MS-DOS, OS/2, and ProDOS disks  
\* Internal 8x-speed CD-ROM drive

### Display

=====  
Built-in display  
-----

- \* 14-in. (12.3-in. diagonal viewable image size) shadow-mask color display
- \* 16-bit-per-pixel RGB color
- \* 640- by 480-pixel resolution
- \* 0.28-mm dot pitch
- \* 66.67-Hz refresh rate
- \* Tilts from -5° to +15°, swivels a full 360°
- \* Front-panel controls for adjusting screen brightness
- \* Very low ELF/VLF emissions

#### Display support

-----s

- \* 16-bit color for display of up to 32,768 colors at 640- by 480-pixel resolution
- \* 1MB video frame buffer (independent of system RAM)

#### Sound

=====

- \* Stereo 16-bit sound
- \* Built-in stereo speakers
- \* Sound-output port
- \* Sound-input port
- \* Front headphone jack and volume control
- \* Built-in monophonic microphone

#### Expansion interfaces

=====

- \* LC processor-direct slot for networking, communications, and multimedia expansion, such as a modem, Ethernet card, or MPEG video card  
– Compatible with most Macintosh Performa 400 and 500 series; Macintosh Quadra 605; Macintosh LC II, LC III, LC 475, LC 550, LC 575, and LC 630; Performa 630; and Performa and Power Macintosh 5200, 5300, 6200, and 6300 series processor-direct cards
- \* Apple Desktop Bus port for mouse, keyboard, and other devices (multiple devices can be connected to each other from one port)
- \* Two RS-232/RS-422 serial ports for an AppleTalk network connection, other networking connections, communications equipment, or a printer (some models include built-in modem that uses one serial port)
- \* SCSI interface port for as many as five external SCSI devices, such as disk drives or CD-ROM drives
- \* Communications slot for Ethernet card or fax/data modem card
- \* Video slot for video-input card (such as the Apple Video System)
- \* TV tuner connector and infrared control sensor for TV tuner card (such as the Apple TV/FM Radio System or the Apple TV/Video System)

#### Electrical requirements

=====

- \* Line voltage: 110 to 240 V AC, RMS, single phase, nominal
- \* Frequency: 50 to 60 Hz
- \* Power: 240 W maximum
- \* U.S. EPA Energy Star compliant

#### Size and weight

=====

- \* Height: 17.5 in. (44.5 cm)
- \* Width: 15.1 in. (38.3 cm)
- \* Depth: 16 in. (40.6 cm)
- \* Weight: 45 lb. (20.5 kg)

Operating environment

=====

- \* Operating temperature: 50° to 104° F (10° to 40° C)
- \* Storage temperature: -40° to 116° F (-40° to 47° C)
- \* Relative humidity: 20% to 95%, noncondensing
- \* Maximum altitude: 10,000 ft. (3,048 m)

Disability access

=====

- \* CloseView software magnifies screen image up to 16 times
- \* Easy Access software permits combination keys to be pressed sequentially and enables cursor control from the numeric keypad instead of the mouse
- \* "Visual beep" replaces audible system alerts

Article Change History:

31 Oct 1996 - Changed distribution status.

Copyright 1996, Apple Computer, Inc.

Tech Info Library Article Number:20414