



# Tech Info Library

## Apple IIGS: Use DuoDisk on Interface Card, NOT on SmartPort

Revised: 6/29/90  
Security: Everyone

Apple IIGS: Use DuoDisk on Interface Card, NOT on SmartPort

=====

This article last reviewed: 2 April 1990

TOPIC -----

I have a "Blockbuster" Apple IIGS with Rev. 3.0 ROM, a DuoDisk, and Profile in slot 7.

I plugged the DuoDisk into the disk port on the Apple IIGS main logic board, installed the ProFile in slot 7, and set the Control Panel to "your card." Leave both DuoDisk drives empty and power on the system. Then I set startup to "Scan."

The DuoDisk LED for drive #1 should turn on, but the system will not start. Why did the Apple IIGS skip the ProFile in slot 7? Then, when I power down the Apple IIGS and put a non-write-protected disk in the DuoDisk drive, it still doesn't start.

If I power down the Apple IIGS and place a write-protected disk in the drive, then power on the system. The system starts up as expected, following the "Control Panel".

If the system appears to be "hung" following any of the above steps, momentarily triggering the write-protect switch by inserting anything into the drive allows the system to start up.

There appears to be compatibility problems with the new Apple IIGS main logic board and the DuoDisk. Performing the "DuoDisk/Apple IIGS fix" that is posted on AppleLink has no effect since the problem appears to be hardware (firmware) based.

What can I do?

DISCUSSION -----

There IS a compatibility problem with the DuoDisk and the Rev 3 Apple IIGS main

logic board. Do not use the DuoDisk on the SmartPort: there is some code in the ROM that does not handle the interface to a DuoDisk properly.

As of April, 1990, the only workaround is to use the DuoDisk on an interface card.

Copyright 1990 Apple Computer, Inc.

Tech Info Library Article Number:5434